ROTO-COMPACTOR

APS 800

System: Standard Comblift








ROTO-COMPACTOR


The APS 800


- achieves maximum cost savings and significant reduction of effort and labour.
- positioning the unit directly where waste is generated saves handling costs.
- utilises manpower significantly as everybody can operate the unit without any training.
- can be fed whilst compacting the waste.
- helps to keep the working environment clean.
- eliminates expensive and space-consuming containers.
- minimum space requirements: needs less than 2m² of area and only 2.30 m of total height.
- can be moved through standard doorways.
- particularly suitable for wet waste and heavy use.
- improves hygiene by discouraging vermin and insects and minimising smells.



 The Roto-Compactor grips, tears and compacts the waste by means of a specially designed steel drum. 2. The wheely bin is emptied by a dust car







Dimensions

Type: APS 800 Technical Specification Own weight: 720 kg Bin-Content: 600 I / 800 I

2.2 kW/380-415 V/50 Hz

Beneficial application for waste disposal and recycling in many industries, including:

- Food industry
- Restaurants
- Catering

Electrical data:

- Hospitals
- Hotels and many more.

BERGMANNs policy is one of continuous improvement, and, accordingly the company reserves the right to alter specifications, weights und dimensions without prior notice.

In printing this brochure, every care has been taken, but specifications and details must not be regarded als binding.



www.bergmann-online.com